

Technical Data Sheet

ScalePro[™]


Scale remover for adiabatically cooled condensers



SPECIAL FEATURES

Rapidly removes limescale from condenser coils

DIRECTIONS OF USE



NOTE: ScalePro[™] is an industrial-strength descaler and therefore acts very quickly. Be sure to understand the inherent risks of using an acid-based chemical on metal surfaces, and rinse thouroughly after using. If you are still unsure, please contact Aspen Pumps Ltd for application advice.

Isolate electrics on the system.

For user safety, avoid using ScalePro[™] in windy conditions. Firstly wet coil with water. Using a low pressure sprayer, spray ScalePro onto the affected area – starting at the bottom in one

corner and progressing methodically up and across. ScalePro™ will bubble on contact with the mineral deposits. The maximum contact time for this product is 2 minutes.

The coil should then be rinsed thoroughly for 15 minutes until all ScalePro[™] is removed.

If any limescale remains, repeat the whole process as necessary.

deposits a thick mineral coating on metal surfaces, restricting airflow and insulating heat-exchange fins. This buildup causes soaring head pressures as the condenser struggles to dissipate heat, eventually leading to system failure. ScalePro™ is a super-fast descaler for condensers affected by this issue.

Limescale is often a serious problem on ill-protected, badly fitted or heavily-used adiabatic condensers. Constant water-cooling guickly

PRODUCT SPECIFICATION

Name	ScalePro™
Product Code	S010147R1
Packing Quantity (ml, L)	4 x 5 Litres
Packing Size (L x H x D cm)	40 x 30 x 27
Shipping Weight (kg)	23.68
Shipping Volume (m3)	0.0324
UFI	NGQ2-Q15Q-E70H-NM3M



ScalePro[™] Warning Contains: Hydrochloric Acid,

H315 - Causes skin irritation. H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. P260 - Do not breathe fume. P264 - Wash hands thoroughly after handling. P280 - Wear eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

This product should only be used by trained operatives. The "directions for use" are recommendations only; correct use will depend upon circumstances. To the extent permitted, no liability can be accepted for loss resulting from its use. Aspen Pumps Ltd follows a policy of continual product improvement. For this reason, some materials and specifications could change without notice. Consult Safety Data Sheet for full safety information. Always wear suitable PPE.

Aspen Pumps Ltd Guardian House, Stroudley Road Basingstoke, Hampshire, RG24 8NL. UK

 T: +44 (0)1323 848842

 E: sales@aspenpumps.com

 aspenpumps.com

 in
 O

05/24