





FLOAT BASED CONDENSATE REMOVAL PUMP

The new Peri Pro+ pump offers outstanding reliability with an industry first 5 year warranty*. Built upon stepper motor technology and software control, this version offers smart pumping technology similar to the latest mini pumps, always minimising audible noise and tube wear.



15L/h max. flow



12m max. head



21 dB(A) @ 1m








- 5 year warranty*
- Configurable motor speed
- Flexible Installation with outstanding lift
- Easy to install with Patented mounting technology

Suitability

- Up to 20 kW (68 000Btu/h)
- High wall split systems; Ducted units; Floor standing & Chassis units
- **Perfect for...** hotel bedrooms and other remote install locations










@ 230 VAC 50Hz		
Max. flow	15 L/h @ 12m head	
Max. head	12m	
Max. suction lift	3m	
dB(A) @1m	21dB(A)	
Power supply	110-230 VAC, 0.2A, 50/60Hz	
Rated	Continuously	
Class	II 🗆	
Max. unit output	20kW (68 000 Btu/h)	
Max. water output	40°C (104°F)	
Inlet/Outlet	6mm ID	
IP Protection	IP24	
Safety Switch	5A NC relay	
Self priming	✓	



	OPTIONS	
Peri Pro+		FP3391

SUGGESTED XTRA ACCESSORIES		
Description	Part No.	
Peri Spare Tube Kit	FP3394	
1 Amp Fuse	FP2620	
Tube Soil Stack Adaptor	FP2038	
For more installation accessories take a		



Peri Pro Air CONDENSATE REMOVAL PUMP • 3m Plug & Play power/sensor cable • Wall mounted bracket • Fixing kit • Installation manual

Download manual at aspenpumps.com

Information correct at time of going to press. Not all products are available in all regions.

* excludes tube and subject to correct installation and operation