







CONDENSATE REMOVAL PUMP

With an impressive flow rate, these robust and reliable Heavy Duty pumps are perfect for the rapid removal of large quantities of condensate water.



HD6: 900L/h max. flow HD10: 1070L/h max. flow

HD6: 6m max. rec. head (flow rate 180L/h) HD10: 9m max. rec. head (flow rate 100L/h)

KEY FEATURES

- High flow rate
- Non return valve
- Easy installation
- 4 litre tank capacity




SUITABILITY


• HD6: Up to 1200kW / 4m Btu/h* HD10: Up to 1460kW / 4.9m Btu/h*

• Humidifiers; Air handling units (AHUs)

. . . .

265mm






HEAVY DUTY 6 & 10 @ 230V 50Hz


Max. flow	HD6: 900L/h, HD10: 1070L/h
Max. rec. head	HD6: 6m, HD10: 9m
Tank capacity	4L
dB(A) @ 1m	HD6: 60, HD10: 64
Power supply	HD6: 230 VAC, 1.5A, 50Hz
	HD10: 230 VAC, 0.38A, 50Hz
Rated	HD6: Non continuous
	HD10: Continuous
Class	l appliance
Max. unit output	HD6: 1200kW / 4m Btu/h*
	HD10: 1460kW / 4.9m Btu/h*
Max. water temp	40°C / 104°F
Inlet/outlet	x2 40mm in,10mm out
IP Protection	IP20
Safety switch	3.0A Normally closed
Information correct at time of going to press.	


HEAVY DUTY 6 & 10 OPTIONS

4.3 kq

Heavy Duty 6 Heavy Duty 10







Download manual at aspenpumps.com



FP2074/2

FP2066/2