







Maxi Orange

CONDENSATE REMOVAL PUMP

Need more performance? Designed for larger units, the Maxi Orange pump gives you the extra power when you need it.





35L/h max. flow



15m max. rec. head (flow rate 10L/h)




35dB(A) @ 1m

KEY FEATURES

- High power motor
- Superior performance
- Submersible secondary reservoir included


SUITABILITY








✓ Perfect for... Large commercial units











Max. flow	35L/h @ 0m head
Max. rec. head	15m
Max. suction lift	2m
dB(A) @ 1m	35
Power supply	230 VAC, 0.11A, 16W, 50/60Hz
Rated	Non continuous
Class	II appliance 🔲
Max. unit output	46kW / 157,000Btu/h
Max. water temp	40°C / 104°F
Discharge tube	6mm ID
IP Protection	IP21
Safety switch	3.0A Normally closed
Thermal protection	✓

MAXI ORANGE @ 230 VAC 50Hz

MAXI ORANGE OPTIONS		
Maxi Orange	FP2210/FIL	
† Pump only		

Maxi Orange pump • 1.5m Plug & play power cable • 16mm Inline Filter • Reservoir • Reservoir lid with 1.5m sensor cable • Submersible reservoir • Anti siphon device • Float & filter • 1.5m Suction tube 6mm ID • 220mm Orange inlet hose 14mm ID • 150mm Vinyl breather tube 6mm ID

Important! Please install the included inline filter

Download manual at aspenpumps.com

View install video at aspenpumps.com

Information correct at time of going to press





Fully potted Self priming



