

# Mighty Bracket™

Mini-split installation is now a one man job! Clips to the mounting bracket of most mini-splits.

### **KEY FEATURES**

- Holds unit securely in place during installation – without damaging walls
- Allows single person installation
- Does not damage walls
- Ideal for most brands of mini-splits that weigh up to 45kg
- Folds for easy storage
- Includes tote bag





SPECIFICATIONS		OPTIONS
Materials of construction	ABS	Description Mighty Bracket™

## Part No. AX3010


## Typical mini split mounting plate Level Adjustment Mounting Hook 6 Support Arm 2 Foot Support Sleeve Sock

#### APPLICATION

Hook onto mini-split mounting plate to hold mini-split unit securely in place while installing refrigerant lines, condensate line and electrical hookup.

#### **USER INSTRUCTIONS**

- 1. Attach Mounting Hooks of Mighty Bracket to the mini-split mounting plate tabs (if no tabs are present on the mounting plate, Mighty Bracket hooks can be attached by screws threaded into the wall stud).
- 2. Place Foot Supports flat against the wall (if necessary to avoid potential wall scratching, place clean towel or cardboard between support foot and wall surface).
- 3. Position Level Adjustment Pins to make Support Arm of the brackets horizontal.
- 4. Position Lift Gates at the end of Support Arms to make sure the unit cannot slide off.
- 5. Place protective Sleeve socks over Gates to avoid scratching the unit.
- 6. Set unit securely onto the top of the Support Arms.
- 7. Connect refrigerant lines.
- 8. Connect condensate drain piping and electrical wiring
- 9. Carefully lift and place the indoor unit onto top tabs of mounting plate.
- 10. While ensuring unit does not fall, carefully remove Mighty Bracket and installation is complete.



Information correct at time of going to press